

SPECapc PTC Creo 3.0 Benchmark

Benchmark System Requirements

- PTC Creo 3.0 build M010 fully licensed
- Microsoft Windows 7 64-bit
- Minimum 1920 x 1080 display resolution
- Minimum 8GB system memory recommended

Benchmark Setup

1. The Creo 3.0 application settings must remain as default.
2. The benchmark may not use any other *config.pro*, *config.sup*, *config.win*, *menu_def.pro*, or *protk.dat* files. These files must be removed from your application install location and user folder before running the benchmark.

Benchmark Execution

1. Set the display resolution to a minimum of 1920 x 1080.
2. If Creo 3.0 is installed at a non-default location, edit the *utilities\runbench.bat* file and change the "PROECMD" variable to the parametric.exe location.
3. To run the benchmark, select Start -> All Programs -> SPECapc -> PTC Creo 3.0 -> SPECapc PTC Creo 3.0.
4. When the benchmark is complete, the results will be displayed in text format. The results are located in the *results* folder in the benchmark installation folder.
5. In order to compare like results, the benchmark will report in the *score.txt* file what level of anti-aliasing is supported by the graphics card that the benchmark was run on so one may compare them to results with the same level of anti-alias support.

Issues

- The benchmark will not run with a trial license of Creo.